

Robust coating thickness gauge

Rugged coating thickness gauge with fixed external probe for all non-magnetic coatings on steel and all insulating coatings on non-ferrous metals.

Ram and impact protected through rubber rimmed casing.

Sensor with newly developed wear-resistant carbide metal tip.

Application

Designed for durability and high precision, MiniTest 650 is the ideal tool for any measuring task in the finishing industry.

The rugged and easy-to-handle thickness gauge combines extended mechanical life on the one hand and high accuracy on the other hand to meet the requirements of any professional user in the shipbuilding, automotive, bridge building, construction or other industries.

According to model, MiniTest 650 is suitable to measure:

- Any non-magnetic coatings such as paint, enamel, chrome and zinc on steel.
- Any insulating coatings on nonferrous metals such as paint, anodising, ceramics on aluminium, copper, zinc die-cast, brass, etc.

Description

The battery-operated gauge features a backlit display and a one meter sensor cable. The newly developed one pole sensor is made of a wear and- tear resistant carbide material to ensure a virtually unlimited life cycle under normal condition use.

An optimal ram and impact protection is provided through the rubber rimmed casing. Via an USB interface, the MiniTest 650 can be connected to a PC for online measurements or display of the statistics.



Physical Testing: Coating Thickness: **MiniTest 650**

MiniTest 650 is available in three different models:

- Model F - with a magnetic-induction sensor for measurements on steel substrates.
- Model N - with an eddy currents sensor for measurements on non-ferrous metals.
- Model FN - with a dual sensor for measuring on both, steel or non-ferrous metals.

Special feature of the FN model - its dual sensor identifies the substrate material. Upon contact with the surface, the gauge automatically switches to the suitable measuring principle based on your application. The measuring principle conforms to the DIN, ISO, BS, and ASTM norms and standards.

Technical specifications

Function	Description
Measuring range	Model F (steel) 0 ... 3000 μm / 120 mils
	Model N (non-ferrous metal) 0 ... 2000 μm / 80 mils
	Model FN (dual sensor) 0 ... 2000 μm / 80 mils
Measuring uncertainty	\pm (2 % of reading + 2 μm) / \pm (2 % of reading + 0.08 mils)
Minimum curvature radius	5 mm / 0.2" convex 25 mm / 1" concave
Minimum measuring area	\varnothing 20 mm / 0.8"
Minimum base thickness	0.5 mm / 20 mils (F) 50 μm / 2 mils (N)
Display	4-digit screen data (11 mm / 0.44")
Measuring units	μm – mils user selectable
Calibration	Standard, 1-point and 2-point calibration
Statistics	Calculated from maximum 9.999 readings, mean value, standard deviation, number of readings, minimum and maximum
Interface	USB
Power supply	3 Micro AAA batteries (for more than 10,000 readings)
Dimensions and weight	Housing: 70 mm x 122 mm x 32 mm / 2.7" x 4.8" x 1.26"
	Sensor: \varnothing 15 mm x 62 mm / \varnothing 0.60" x 2.44"; 225 grams / 7.93 ozs
Ambient temperature	Gauge: 0 to 50 °C / 32 ° to 122 °F
	Sensor: -10 ° to 70 °C / 14 ° to 158 °F

Standard supply includes:

- Gauge with sensor and three batteries
- Control standard(s) and calibration standard(s)
- Operating instructions
- Soft pouch.

Physical Testing: Coating Thickness: **MiniTest 650**

Ordering information

Product Ref	Description
SHMINITEST650F	MiniTest 650F - Including Stats Probe. Ferrous 0-3000µM / 120 Mils
SHMINITEST650N	MiniTest 650N - Including Stats Probe. Non-Ferrous 0-2000µM / 80 Mils
SHMINITEST650FN	MiniTest 650FN - Including Stats Probe. Ferrous/Non-Ferrous 0-2000µM / 80 Mils

Owing to continuous development, we reserve the right to introduce improvements and modify specifications without prior notice.

**Our sales team can be contacted on:
info@sheeninstruments.com or +44 (0)208 783 4321**